


9.炭素鋼・ステンレス鋼鍛鋼製突合溶接型 SCH40 SCH80 SCH160



同径ウエルドオーレット

品番	STD & SCH 40	XS & SCH 80	XXS & SCH 160
	419W	819W	919W

単位 mm

径の呼び	A			B			C			D		
	STD & SCH40	XS & SCH80	XXS & SCH160	STD & SCH40	XS & SCH80	XXS & SCH160	STD & SCH40	XS & SCH80	XXS & SCH160	STD & SCH40	XS & SCH80	XXS & SCH160
1/2	19.1	19.1	28.7	35.1	35.1	35.1	23.9	23.9	14.2	16.0	16.0	14.2
3/4	22.4	22.4	31.8	44.5	44.5	44.5	30.2	30.2	19.1	20.6	20.6	19.1
1	26.9	26.9	38.1	54.1	54.1	50.8	36.6	36.6	25.4	26.2	26.2	25.4
1 1/4	31.8	31.8	44.5	65.0	65.0	62.0	44.5	44.5	33.3	35.1	35.1	33.3
1 1/2	33.3	33.3	50.8	73.2	73.2	69.9	50.8	50.8	38.1	41.4	41.4	38.1
2	38.1	38.1	55.6	88.9	88.9	81.0	65.0	65.0	42.9	52.3	52.3	42.9
2 1/2	41.4	41.1	62.0	103.1	103.1	96.8	76.2	76.2	54.1	62.0	62.0	54.1
3	44.5	44.5	73.2	122.2	122.2	120.7	93.7	93.7	73.2	77.7	77.7	73.2
3 1/2	50.8	50.8	-	143.0	143.0	-	109.5	109.5	-	90.4	90.4	-
4	50.8	50.8	84.1	152.4	152.4	152.4	120.7	120.7	98.6	101.6	101.6	98.6
5	57.2	57.2	93.7	185.7	185.7	187.5	147.6	147.6	122.2	128.5	128.5	122.2
6	60.5	77.7	104.9	215.9	219.2	212.9	169.9	169.9	146.1	153.9	153.9	146.1
8	69.9	98.6		263.9	270.0		220.7	220.7		201.7	193.8	
10	77.7	88.9		323.1	323.9		274.6	265.2		254.0	247.7	
12	85.9	100.1		378.0	379.5		325.4	330.2		304.8	298.5	
14	88.9	104.9		410.0	414.3		357.1	363.5		336.6	330.2	
16	93.7	112.8		464.1	466.9		407.9	419.1		387.4	381.0	
18	103.1	119.1		521.0	524.0		473.2	473.2		438.2	431.8	
20	117.6	127.0		572.0	582.7		509.5	528.6		489.0	482.6	
24	136.7	139.7		690.1	708.2		638.3	638.3		590.6	584.2	
30	136.7	181.1		866.9	889.0		773.2	762.0		743.0	736.6	
36	136.7	212.9		1030.0	1055.1		927.1	914.4		895.4	889.0	